

# BEX F serie vlakstraalsproeiers vervolg

**VLAKSTRAAL**

Sproei- hoek bij 3 bar	Capaciteits- nummer	Aansl. buitendr. BSPT	equivalent boring Ø in mm	Capaciteit in liters per minuut bij verschillende drukken in bar														Sproeihoek		
				0.3 bar	0.5 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar	5 bar	7 bar	10 bar	20 bar	30 bar	1.5 bar	3 bar	5 bar	
80°	B1/8F8030	1/8	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	75°	80°	86°	
	B1/4F8030	1/4	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	75°	80°	86°	
	B3/8F8030	3/8	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	75°	80°	86°	
	B1/8F8040	1/8	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	76°	80°	85°	
	B1/4F8040	1/4	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	76°	80°	85°	
	B3/8F8040	3/8	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	76°	80°	85°	
	B1/4F8050	1/4	4.24	6.2	8.1	9.5	11.4	14.0	16.1	19.7	22.8	25.5	30.1	36	51	62	77°	80°	84°	
	B3/8F8050	3/8	4.24	6.2	8.1	9.5	11.4	14.0	16.1	19.7	22.8	25.5	30.1	36	51	62	77°	80°	84°	
	B1/4F8060	1/4	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	77°	80°	84°	
	B3/8F8060	3/8	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	77°	80°	84°	
	B1/2F8060	1/2	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	78°	80°	84°	
	B1/4F8070	1/4	5.00	8.7	11.3	13.3	16.0	19.5	22.6	27.6	32	36	42	50	71	87	78°	80°	87°	
	B3/8F8070	3/8	5.00	8.7	11.3	13.3	16.0	19.5	22.6	27.6	32	36	42	50	71	87	78°	80°	87°	
	B1/2F8070	1/2	5.00	8.7	11.3	13.3	16.0	19.5	22.6	27.6	32	36	42	50	71	87	78°	80°	87°	
	B1/4F8080	1/4	5.36	10.0	12.9	15.3	18.2	22.3	25.8	32	36	41	48	58	82	100	78°	80°	88°	
	B3/8F8080	3/8	5.36	10.0	12.9	15.3	18.2	22.3	25.8	32	36	41	48	58	82	100	78°	80°	88°	
	B1/2F8080	1/2	5.36	10.0	12.9	15.3	18.2	22.3	25.8	32	36	41	48	58	82	100	78°	80°	88°	
	B3/8F80100	3/8	5.99	12.5	16.1	19.1	22.8	27.9	32	39	46	51	60	72	102	125	75°	80°	83°	
	B1/2F80100	1/2	5.99	12.5	16.1	19.1	22.8	27.9	32	39	46	51	60	72	102	125	75°	80°	83°	
	B3/8F80150	3/8	7.34	18.7	24.2	28.6	34	42	48	59	68	76	90	108	153	187	73°	80°	84°	
	B1/2F80150	1/2	7.34	18.7	24.2	28.6	34	42	48	59	68	76	90	108	153	187	73°	80°	84°	
	B1/2F80200	1/2	8.46	25.0	32	38	46	56	64	79	91	102	121	144	204	250	74°	80°	82°	
	B3/4F80200	3/4	8.46	25.0	32	38	46	56	64	79	91	102	121	144	204	250	74°	80°	82°	
	B3/4F80400	3/4	11.96	50	64	76	91	112	129	158	182	204	241	288	408	499	74°	80°	82°	
65°	B1/8F65015	1/8	0.79	0.19	0.24	0.29	0.34	0.42	0.48	0.59	0.68	0.76	0.90	1.1	1.5	1.84	51°	65°	75°	
	B1/4F65015	1/4	0.79	0.19	0.24	0.29	0.34	0.42	0.48	0.59	0.68	0.76	0.90	1.1	1.5	1.84	51°	65°	75°	
	B1/8F6502	1/8	0.91	0.25	0.32	0.38	0.46	0.56	0.64	0.79	0.91	1.0	1.2	1.4	2.0	2.45	52°	65°	74°	
	B1/4F6502	1/4	0.91	0.25	0.32	0.38	0.46	0.56	0.64	0.79	0.91	1.0	1.2	1.4	2.0	2.45	52°	65°	74°	
	B1/8F6503	1/8	1.1	0.37	0.48	0.57	0.68	0.84	0.97	1.18	1.37	1.53	1.81	2.2	3.10	3.80	53°	65°	73°	
	B1/4F6503	1/4	1.1	0.37	0.48	0.57	0.68	0.84	0.97	1.18	1.37	1.53	1.81	2.2	3.10	3.80	53°	65°	73°	
	B1/8F6504	1/8	1.2	0.5	0.64	0.76	0.91	1.12	1.29	1.58	1.82	2.0	2.4	2.9	4.1	5.0	53°	65°	73°	
	B1/4F6504	1/4	1.2	0.5	0.64	0.76	0.91	1.12	1.29	1.58	1.82	2.0	2.4	2.9	4.1	5.0	53°	65°	73°	
	B1/8F6505	1/8	1.35	0.62	0.81	0.95	1.14	1.40	1.61	1.97	2.28	2.55	3.01	3.6	5.1	6.2	53°	65°	72°	
	B1/4F6505	1/4	1.35	0.62	0.81	0.95	1.14	1.40	1.61	1.97	2.28	2.55	3.01	3.6	5.1	6.2	53°	65°	72°	
	B1/8F6506	1/8	1.47	0.75	0.97	1.14	1.37	1.67	1.93	2.37	2.73	3.06	3.6	4.3	6.1	7.5	54°	65°	72°	
	B1/4F6506	1/4	1.47	0.75	0.97	1.14	1.37	1.67	1.93	2.37	2.73	3.06	3.6	4.3	6.1	7.5	54°	65°	72°	
	B1/8F6508	1/8	1.70	1.00	1.29	1.53	1.82	2.23	2.58	3.2	3.6	4.1	4.8	5.8	8.2	10.0	55°	65°	71°	
	B1/4F6508	1/4	1.70	1.00	1.29	1.53	1.82	2.23	2.58	3.2	3.6	4.1	4.8	5.8	8.2	10.0	55°	65°	71°	
	B1/8F6510	1/8	1.91	1.25	1.61	1.91	2.28	2.79	3.2	3.9	4.6	5.1	6.0	7.2	10.2	12.5	57°	65°	73°	
	B1/4F6510	1/4	1.91	1.25	1.61	1.91	2.28	2.79	3.2	3.9	4.6	5.1	6.0	7.2	10.2	12.5	57°	65°	73°	
	B3/8F6510	3/8	1.91	1.25	1.61	1.91	2.28	2.79	3.2	3.9	4.6	5.1	6.0	7.2	10.2	12.5	57°	65°	73°	
	B1/8F6512	1/8	2.08	1.50	1.93	2.29	2.73	3.3	3.9	4.7	5.5	6.1	7.2	8.6	12.2	15.0	59°	65°	71°	
	B1/4F6512	1/4	2.08	1.50	1.93	2.29	2.73	3.3	3.9	4.7	5.5	6.1	7.2	8.6	12.2	15.0	60°	65°	72°	
	B1/8F6515	1/8	2.31	1.87	2.42	2.86	3.4	4.2	4.8	5.9	6.8	7.6	9.0	10.8	15.3	18.7	59°	65°	72°	
	B1/4F6515	1/4	2.31	1.87	2.42	2.86	3.4	4.2	4.8	5.9	6.8	7.6	9.0	10.8	15.3	18.7	59°	65°	72°	
	B3/8F6515	3/8	2.31	1.87	2.42	2.86	3.4	4.2	4.8	5.9	6.8	7.6	9.0	10.8	15.3	18.7	60°	65°	72°	
	B1/8F6520	1/8	2.67	2.50	3.2	3.8	4.6	5.6	6.4	7.9	9.1	10.2	12.1	14.4	20.4	25.0	61°	65°	72°	
	B1/4F6520	1/4	2.67	2.50	3.2	3.8	4.6	5.6	6.4	7.9	9.1	10.2	12.1	14.4	20.4	25.0	61°	65°	72°	
	B3/8F6520	3/8	2.67	2.50	3.2	3.8	4.6	5.6	6.4	7.9	9.1	10.2	12.1	14.4	20.4	25.0	61°	65°	72°	
	B1/8F6530	1/8	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	62°	65°	72°	
	B1/4F6530	1/4	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	62°	65°	72°	
	B3/8F6530	3/8	3.28	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	18.1	21.6	30.6	37	62°	65°	72°	
	B1/8F6540	1/8	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	63°	65°	72°	
	B1/4F6540	1/4	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	63°	65°	72°	
	B3/8F6540	3/8	3.78	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	24.1	28.8	41	50	64°	65°	74°	
	B1/4F6550	1/4	4.24	6.2	8.1	9.5	11.4	14.0	16.1	19.7	22.8	25.5	30.1	36	51	62	63°	65°	73°	
	B3/8F6550	3/8	4.24	6.2	8.1	9.5	11.4	14.0	16.1	19.7	22.8	25.5	30.1	36	51	62	63°	65°	73°	
	B1/2F6550	1/2	4.24	6.2	8.1	9.5	11.4	14.0	16.1	19.7	22.8	25.5	30.1	36	51	62	63°	65°	74°	
	B1/4F6560	1/4	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	63°	65°	73°	
	B3/8F6560	3/8	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	63°	65°	73°	
	B1/2F6560	1/2	4.62	7.5	9.7	11.4	13.7	16.7	19.3	23.7	27.3	30.6	36	43	61	75	63°	65°	73°	
	B1/4F6570	1/4	5.00	8.7	11.3	13.3	16.0	19.5	22.6	27.6	32	36	42	50	71	87	63°	65°	74°	
	B3/8F6570	3/8	5.00	8.7	11.3	13.3	16.0	19.5	22.6	27.6	32	36	42	50	71	87	63°	65°	74°	

Enkele maten zijn slechts leverbaar in kunststof.

Voor levering in NPT dient de B voorafgaande aan het schroefdraad te worden vervangen door een N.

Vervolg op de volgende pagina