


Volkegelsproeiers uit de series SM, SM-W en SF-W



Aansluiting	Capaciteitsnr. buitendraad	Capaciteitsnr. binnendraad	boring in mm.	vrije doorkomst in mm	Verschillende drukken in bar											Sproeihoek			
					0,3	0,5	0,7	1	1,5	2	2,5	3	4	5	6	0,3 bar	0,7 bar	3 bar	5 bar
					Capaciteit (liter/min.)														
1/8"	B1/8 SM2,8W		1,59	1,02	0,73	0,92	1,07	1,25	1,49	1,7	1,87	2,03	2,31	2,54	2,76	90°	120°	120°	102°
	B1/8SM4,3W		1,98	1,02	1,13	1,41	1,64	1,92	2,29	2,61	2,88	3,12	3,54	3,91	4,24	98°	120°	120°	102°
	B1/8SM5,6W		2,38	1,02	1,47	1,84	2,13	2,5	2,99	3,39	3,75	4,06	4,61	5,09	5,52	98°	120°	120°	102°
	B1/8SM8W		2,38	1,27	2,1	2,63	3,05	3,57	4,27	4,85	5,35	5,8	6,59	7,27	7,88	98°	120°	120°	103°
1/4"	B1/4SM2,8W		1,59	1,02	0,73	0,92	1,07	1,25	1,49	1,7	1,87	2,03	2,31	2,54	2,76	90°	120°	120°	102°
	B1/4S4,3W		1,98	1,02	1,13	1,41	1,64	1,92	2,29	2,61	2,88	3,12	3,54	3,91	4,24	98°	120°	120°	102°
	B1/4S5,6W		2,38	1,02	1,47	1,84	2,13	2,5	2,99	3,39	3,75	4,06	4,61	5,09	5,52	98°	120°	120°	102°
	B1/4SM8W		2,38	1,27	2,1	2,63	3,05	3,57	4,27	4,85	5,35	5,8	6,59	7,27	7,88	98°	120°	120°	103°
	B1/4SM10W		2,78	1,27	2,62	3,28	3,81	4,46	5,34	6,06	6,69	7,25	8,23	9,09	9,85	112°	120°	120°	103°
	B1/4SM12W		3,18	1,27	3,14	3,94	4,57	5,35	6,4	7,27	8,03	8,7	9,88	10,9	11,82	114°	120°	120°	103°
	B1/4SM14W		3,57	1,59	3,67	4,6	5,34	6,25	7,47	8,49	9,36	10,15	11,53	12,72	13,79	114°	120°	120°	103°
	B1/4SM16W		3,97	1,59	4,45	5,58	6,48	7,58	9,07	10,3	11,37	12,33	14	15,45	16,74	114°	120°	120°	103°
3/8"	B3/8SM17W		4,37	2,38	5,24	6,57	7,62	8,92	10,67	12,12	13,38	14,5	16,47	18,17	19,7	114°	120°	121°	104°
	B3/8SM20W		4,76	2,38	6,29	7,88	9,15	10,71	12,81	14,55	16,05	17,4	19,76	21,81	23,64	114°	120°	121°	104°
	B3/8SM24W		5,16	2,78	7,08	8,87	10,29	12,05	14,41	16,36	18,06	19,58	22,23	24,54	26,59	114°	120°	121°	106°
	B3/8SM27W		5,56	2,78	7,86	9,85	11,43	13,38	16,01	18,18	20,07	21,75	24,7	27,26	29,55	114°	120°	121°	108°
1/2"	B1/2SM30W		5,95	3,18	9,17	11,49	13,34	15,62	18,68	21,21	23,41	25,38	28,82	31,8	34,47	114°	120°	121°	108°
	B1/2SM40W		6,35	3,18	10,48	13,14	15,24	17,85	21,35	24,24	26,76	29	32,93	36,35	39,4	114°	120°	121°	108°
	B1/2SM45W		6,35	3,57	11,79	14,78	17,15	20,08	24,02	27,27	30,1	32,63	37,05	40,89	44,32	114°	120°	121°	110°
	B1/2SM50W		6,75	3,97	13,1	16,42	19,05	22,31	26,69	30,3	33,45	36,25	41,17	45,44	49,25	114°	120°	121°	112°
	B3/4SM6W		9,92	4,37	18,41	23,07	26,77	31,34	37,49	42,57	46,99	50,93	57,84	63,83	69,19	115°	120°	121°	112°
1"	1SM11W		13,1	5,56	33,75	42,29	49,08	57,46	68,73	78,05	86,14	93,37	106,04	117,03	126,85	117°	120°	124°	117°
1-1/4"	1-1/4SF16W		15,48	6,35	49,09	61,52	71,38	83,57	99,98	113,53	125,3	135,82	154,23	170,22	184,51	118°	121°	124°	119°
	1-1/4SF20W		15,88	6,35	61,36	76,9	89,23	104,47	124,97	141,92	156,63	169,77	192,79	212,78	230,63	118°	124°	130°	122°
	1-1/4SF22W		16,67	10,32	67,49	84,59	98,15	114,91	137,47	156,11	172,29	186,75	212,07	234,05	253,7	119°	125°	130°	122°
1-1/2"	1-1/2SF24W		18,26	10,32	73,63	92,28	107,08	125,36	149,97	170,3	187,95	203,73	231,35	255,33	276,76	119°	124°	125°	119°
2"	2SF47W		25	11,11	144,19	180,71	209,69	245,5	293,68	333,5	368,07	398,96	453,06	500,02	541,99	120°	124°	125°	119°
2-1/2"	2-1/2SF70W		31,75	14,29	214,75	269,15	312,3	365,63	437,4	496,71	548,19	594,2	674,77	744,72	807,21	120°	125°	125°	119°
3"	3SF95W		34,93	17,46	291,45	365,27	423,84	496,22	593,61	674,1	743,98	806,42	915,76	1010,68	1095,5	120°	125°	125°	119

Afmetingen

Aansluiting buitendraad Model SM			
maat	model	lengte	s/w
1/8"	1/8SM	20 mm.	12 mm.
1/4"	1/4SM	23 mm.	14 mm.
3/8"	3/8SM	25 mm.	17 mm.
1/2"	1/2SM	32 mm.	22 mm.
3/4"	3/4SM	36 mm.	27 mm.
1"	1SM	50 mm.	38 mm.

Aansluiting buitendraad Model SM-W				Aansluiting binnendraad Model SF-W			
maat	model	lengte	s/w	maat	model	lengte	diameter
1/8"	1/8SM-W	18 mm.	11 mm.	1"	1SM-W	68 mm.	38 mm.
1/4"	1/4SM-W	25 mm.	14 mm.	1-1/4"	1-1/4SF-W	88 mm.	53 mm.
3/8"	3/8SM-W	26 mm.	18 mm.	1-1/2"	1-1/2SF-W	103 mm.	59 mm.
1/2"	1/2SM-W	32 mm.	21 mm.	2"	2SF-W	137 mm.	78 mm.
3/4"	3/4SM-W	36 mm.	27 mm.	2-1/2"	2-1/2SF-W	162 mm.	87 mm.
				3"	3-SF-W	196 mm.	105 mm.